

Dependent Resurvey, Portion, S. Bdy.,  
T. 12 N., R. 29 E., Mt. Diablo Mer., Nevada

CHAINS  
4.35

The  $\frac{1}{4}$  sec. cor. of sec. 6 only, monumented with an iron post, 1 in. diam., firmly set, protruding 12 ins. above ground, with brass cap mkd.

$\frac{1}{4}$  S 6  
1929

Rebuild the mound of stone, 3 ft. base, 2 ft. high, S. of cor.

Cor. falls 1 lk. N. of a fence bearing E. and W.

East, beginning new measurement.

Desc. over ESE. slope.

3.62

The meander cor. of sec. 6 only, monumented with the rusted stub of the iron post, 1 in. diam., firmly set, broken 6 ins. below the surface. This cor. will now also function as the NW. cor. of Tract No. 39, T. 11 N., R. 29 E.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T 12 N  
TR-40  
S 6 / MC  
T 11 N / TR-39  
R 29 E  
1973

Deposit the remains of the original iron post alongside the new iron post.

Cor. falls 2 lks. N. of a fence bearing E. and W.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 12 N., R. 29 E., Mount Diablo Meridian, Nevada

(Restoring a portion of the 1904 survey  
by H. E. Franks and J. S. Mullen, U.S. Deputy Surveyors)

From the cor. of secs. 17, 18, 19, and 20, monumented with an iron rod, not of known record, 1 in. diam., firmly set, protruding 8 ins. above ground. Pieces of a wooden post, scribing visible but not legible, are scattered on the ground around the cor. The original granite stone, 13 x 10 x 9 ins., mkd. with 3 notches on the S. and 5 notches on the E. edges, is firmly set, top 12 ins. below the surface, under the iron rod.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.