Survey, Portions, 2nd Stan. Par. N., T. 11 N., R. 29 E., Mt. Diablo Mer., Nevada

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

Continue descent over WSW. slope.

Point for a meander cor. on the water's edge on the E. side of Walker Lake, identical with Angle Pt. No. 3 of Tract No. 37.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a stove pipe, 6 ins. diam., cement filled to top, with brass cap mkd.

Land, low, rolling sand dunes and gravel flats. Soil, sand and gravel. Vegetation, scattering shadscale and sagebrush.

Survey of Tract No. 37, T. 11 N., R. 29 E., Mount Diablo Meridian, Nevada

Beginning at Angle Pt. No. 1 of Tract No. 37, identical with the original meander cor. of secs. 26 and 35, and the southeasterly cor. of Tract No. 38, hereinbefore described.

West, on line 1-2 of Tract No. 37, identical with the S. bdy. of Tract No. 38, crossing the former bed of Walker Lake.

Desc. over WSW. slope, crossing low, rolling sand dunes, through scattering undergrowth.

44.90 Point selected for a witness point.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

Continue descent over WSW. slope.

Point for Angle Pt. No. 2 of Tract No. 37, which is a meander cor. bet. Tract No. 37 and Tract No. 38, on the water's edge on the E. side of Walker Lake.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a stove pipe, 6 ins. diam., cement filled to top, with brass cap mkd.