## Dependent Resurvey of the N. Bdy., T. 32 N., R. 32 E., M.D.M., Nevada

	1. 32 N., R. 32 E., M.D.M., Nevada
CHAINS	Set a steel fence post, 5-1/2 ft. long, alongside the iron post.
	S. 89° 43' W., bet. secs. 5 and 32.
	Asc. 60 ft. over E. slope to the 1/4 sec. cor., through medium growth of shadscale.
22.90	Road, bears N. 80° W. and S. 80° E.
39.72	Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2-1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 33 N R 32 E 1/4 S 32 T 32 N
	1974
	Set a steel fence post, 5-1/2 ft. long, alongside the iron post.
	Asc. 120 ft. over E. slope to the sec. cor.
41.30	Wash, 10 1ks. wide, 1 ft. deep, drains S. 40° E.
71.50	Wash, 10 1ks. wide, 1 ft. deep, drains N. 85° E.
79.44	The cor. of secs. 5, 6, 31 and 32, perpetuated with a mound of stone, 3 ft. base, 6 ins. high. This position is harmoniously related to other existing original cors. and is accepted as the best available evidence of the position of the original cor.
	At the corner point
	Set an iron post, 28 ins. long, 2-1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 33 N R 32 E S 31   S 32 S 6   S 5 T 32 N 1974
	Set a steel fence post, 5-1/2 ft. long, alongside the iron post.
	S. 89° 56' W., bet. secs. 6 and 31.
	Asc. 50 ft. over broken E. slope, through medium
	growth of shadscale, greasewood and budsage.
13.80	Road, bears N. 15° W. and S. 15° E.; asc. 60 ft. over NE. slope.