

Dependent Resurvey of
T. 32 N., R. 33 E., M.D.M., Nevada

CHAINS	<p>The geographic position of the Southeast corner of the township, as calculated from U.S.C. & G.S. stations "ROYAL" and "HOUSE" is as follows:</p> <p>Latitude 40° 35' 17.0" N. Longitude 118° 11' 56.4" W.</p> <p>The mean magnetic declination is 18° East.</p>
	<p>Dependent Resurvey of the South Boundary of T. 32 N., R. 33 E., Mount Diablo Meridian, Nevada</p>
	<p>Reestablishment of the survey executed by E.H. Dyer, Deputy Surveyor, in 1863 and the Resurveys executed by H.B. Maxson, Deputy Surveyor, in 1893; F.H. Criss, Deputy Surveyor, in 1901; Thomas A. Haigh, U.S. Surveyor, in 1913; and Emil Voigt, Cadastral Engineer, in 1939.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the point for the standard cor. of Tps. 32 N., Rs. 32 and 33 E., as described in the field notes of the dependent resurvey of the South bdy. of T. 32 N., R. 32 E., of this Group.</p> <p>S. 89° 55' E., on the South bdy. of sec. 31.</p> <p>Across Rye Patch Reservoir.</p>
26.20	<p>High water line of Rye Patch Reservoir bears N. 20° W. and S. 20° E.; over nearly level land, through medium undergrowth of shadscale.</p>
27.32	<p>Set an iron post, 28 ins. long, 2-1/2 ins. diam., 22 ins. in the ground for a witness point, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>W P T 32 N R 33 E S 31 <u>1974</u></p> </div> <p>Set a steel fence post, 5-1/2 ft. long, alongside the iron post.</p>
32.80	<p>Head of wash, drains S.</p>
39.79	<p>The Voigt (1939) standard 1/4 sec. cor. of sec. 31 monumented with an iron post, 1 in. diam., firmly set, exposed 8 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p><u>1/4 S 31</u> 1939</p> </div> <p>with a mound of stone, 2 ft. base, 1-1/2 ft. high, N. of cor.</p> <p>Brass cap remkd.</p>