

Dependent Resurvey of the  
S. Bdy., T. 32 N., R. 33 E., M.D.M., Nevada

CHAINS	
39.20	Ravine, drains NW.
39.39	<p>The Maxson (1893) standard 1/4 cor. of sec. 35, perpetuated with a 16 X 8 X 8 ins. quartzite rock in a mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2-1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T 32 N R 33 E 1/4 S 35 1974</p> <p>Bury the quartzite stone alongside the iron post and set a steel fence post, 5-1/2 ft. long, 22 ins. in the ground, alongside the iron post. Raise a mound of stone N., 3 ft. base, 2 ft. high.</p> <p>The Criss (1901) standard 1/4 cor. of sec. 35, monumented with a granite stone, 16 X 11 X 10 ins., firmly set, mkd. 1/4 on N. face, bears N. 52° 26' E., 2.28 chs. dist., mkd. AM and buried.</p> <p style="text-align: center;">_____</p> <p>N. 88° 34' E., beginning new measurement.</p> <p>Over mountainous land; asc. 300 ft. over broken W. slope to ridge.</p>
9.51	The Maxson closing cor. of secs. 1 and 2, T. 31 N., R. 33 E., monumented with a quartzite rock, 17 X 13 X 7 ins., firmly set in a mound of stone, mkd. C.C. on S. face, bears North, 1.19 chs. dist.
24.50	Ridge, bears NW. and SE.; desc. 30 ft.
27.70	Ravine, drains NW.; asc. 70 ft. over SW. slope.
31.30	Ridge, bears N. and S.; desc. 170 ft. over E. slope.
37.50	Ravine, drains N. 20° E.; asc. 60 ft. over SSW. slope.
39.25	The Maxson (1893) standard cor. of secs. 35 and 36, monumented with a quartzite stone, 18 X 10 X 7 ins., no marks, firmly set in a mound of stone, 2 ft. base, 1 ft. high, bears South, 0.88 chs. dist.
39.70	Spur, slopes N.; desc. 10 ft. over E. slope.
40.37	The Criss (1901) standard cor. of secs. 35 and 36, perpetuated with a mound of stone, 3 ft. base, 1 ft. high. This position is harmoniously