

Dependent Resurvey of the
S. Bdy., T. 32 N., R. 33 E., M.D.M., Nevada

CHAINS	
	<p>related to existing original cors. and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2-1/2 ins. diam., 12 ins. in the ground and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>S C T 32 N R 33 E <u>S 35 S 36</u> 1974</p> </div>
	<p>N. 89° 19' E., on South bdy. of sec. 36.</p> <p>Desc. 90 ft. through medium growth of shadscale.</p>
4.30	Enter valley, bears N. and S. over nearly level land.
8.10	Humboldt Canyon, 10 lks. wide, 6 ft. deep, course NW.; asc. 10 ft. over WSW. slope.
9.20	Driveway, bears N. 20° W. and S. 20° E.
11.30	Stream, drains N. 60° W.
12.20	Road, bears N. 60° W. and S. 60° E., leave valley; asc. 300 ft. over SW. slope.
21.10	Spur, slopes SW.; desc. 20 ft. over SE. slope.
24.20	Ravine, drains S. 30° W.; asc. 120 feet over WSW. slope.
29.90	Top of rocky ridge, bears N. and S.; desc. 60 ft. over SE. slope.
35.20	Ravine, drains S. 25° E.
37.60	Ravine, drains S. 40° W.; asc. 10 ft. over SW. slope.
38.37	The Maxson (1893) standard 1/4 sec. cor. of sec. 36, monumented with a granite stone, 18 X 10 X 6 ins., mkd. 1/4 on N. face and firmly set in a mound of stone, 2 ft. base, 1 ft. high, bears South, 1.80 chs. dist.
40.34	The Criss (1901) standard 1/4 sec. cor. of sec. 36, monumented with a granite stone, 14 X 11 X 6 ins., mkd. 1/4 SC, firmly set.
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2-1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>