Dependent Resurvey of the S. Bdy., T. 32 N., R. 33 E., M.D.M., Nevada

CHAINS

base to top, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 32 N., R. 34 E., bears S. 1° 37' W., 3.10 chs. dist.

From this same corner, the 1/4 sec. cor. of sec. 31, T. 32 N., R. 34 E., monumented with an iron post, 2-1/2 ins. diam., firmly set, exposed 6 ins. above the ground, with a steel fence post set alongside the iron post, mkd. as described in the field notes of the dependent resurvey of T. 32 N., R. 34 E., bears N. 1° 37' E., 35.94 chs. dist.

From this same corner, the A.M. monumented with an iron post, 2-1/2 ins. diam., firmly set, exposed 16 ins. above ground and in a mound of stone, 4 ft. base to top, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 32 N., R. 34 E., bears N. 89° 47' E., 1.73 chs. dist.

Dependent Resurvey of the West Boundary of T. 32 N., R. 33 E., M.D.M., Nevada

(Reestablishment of the survey executed by E.H. Dyer, Deputy Surveyor, in 1863 and the resurvey executed by Emil Voigt, Cadastral Engineer, in 1939).

From the point for the standard cor. of Tps. 32 N., Rs. 32 and 33 E., as described in the field notes of the dependent resurvey of the South bdy. of T. 32 N., R. 32 E., under this Group.

N. 0° 26' W., bet. secs. 31 and 36.

Across Rye Patch Reservoir.

36.30 High water line of Rye Patch Reservoir, bears N. 50° W. and S. 50° E.; leave reservoir.

The 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 1 in. diam., exposed 6 ins. above the ground, with brass cap mkd.

Brass cap remkd.

T 32 N 1/4 R 32 E R 33 E S 36|S 31 1974 1939