		Depen	Resurvey			of	the		
N.	Bdy.,	T. 32	Ν.,	R.	33	Ε.,	Μ.	D.M.,	Nevada

The cor. of secs. 5, 6, 31 and 32, monumented with an iron post, 2 ins. diam., exposed 8 ins. above the ground, with brass cap mkd.

Set a steel fence post, 5-1/2 ft. long, alongside the iron post.

S. 89° 41' W., bet. secs. 6 and 31.

Over nearly level land, through medium growth of shadscale, greasewood and budsage.

- 5.40 Road, bears NW. and SE.
- Set an iron post, 2-1/2 ins. diam., 28 ins. long, 22 ins. in the ground for a witness point, with brass cap mkd.

Set a steel fence post, 5-1/2 ft. long, alongside the iron post.

- 31.40 High water line of Rye Patch Reservoir, bears N. and S., across reservoir.
- Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original cor., falls in reservoir and was not monumented.
- Point for the cor. of Tps. 32 and 33 N., Rs. 32 and 33 E., as described in the field notes of the dependent resurvey of the North bdy. of T. 32 N., R. 32 E., of this Group.

Dependent Resurvey of the Subdivisional Lines, T 32 N., R. 33 E., M.D.M., Nevada

(Reestablishment of the surveys executed by E.H. Dyer, Deputy Surveyor, in 1863; the surveys executed by F.H. Criss, Deputy Surveyor, in 1901; the resurveys executed by Thomas A. Haigh, U.S. Surveyor, in 1913; and the resurveys executed by Emil Voigt, Cadastral Engineer, in 1939).