

Dependent Resurvey of the Subdivisional
Lines, T. 32 N., R. 33 E., M.D.M., Nevada

CHAINS	
	N. 89° 54' E., beginning new measurement. Desc. 40 ft. over E. slope.
3.00	Ravine, drains N. 25° E.; asc. 60 ft. over W. slope.
12.40	Ridge, bears N. 20° W. and S. 20° E.; desc. 10 ft. over E. slope.
13.90	Ravine, drains N. 20° W.; asc. 110 ft. over W. slope.
23.90	Ridge, bears N. 20° W. and S. 20° E.; desc. 60 ft. over E. slope.
28.80	Ravine, drains N. 20° W.; asc. 80 ft. over W. slope.
32.90	Ridge, bears N. 20° W. and S. 20° E.; desc. 20 ft. over E. slope.
36.20	Ravine, drains N. 5° W.; asc. 70 ft. over W. slope.
39.69	The Criss (1901) cor. of secs. 24 and 25, monumented with a limestone, 24 X 11 X 8 ins., firmly set in a collar of stone and exposed 12 ins. above the ground, plainly mkd. 2 grooves on S. face and 4 grooves on N. face, in a fence, bearing SSE. and NNW. At the corner point Set an iron post, 28 ins. long, 2-1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. A M 1974 Bury the mkd. stone and set a steel fence post, 5-1/2 ft. long, alongside the iron post.
40.72	Intersect the West bdy. of T. 32 N., R. 34 E. Point for the closing cor. of secs. 24 and 25. Set an iron post, 28 ins. long, 2-1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. T 32 N R 33 E R 34 E CC $\frac{S\ 24}{S\ 25}$ S 19 1974 Set a steel fence post, 5-1/2 ft. long, alongside the iron post. From this corner, the cor. of secs. 19 and 30, T. 32 N., R. 34 E., monumented with an iron post, 2-1/2 ins. diam., firmly set, exposed 8 ins. above the ground and in a mound of stone, 4 ft. base to top, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 32 N., R. 34 E., bears S. 1° 30' W., 3.86 chs. dist.