

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 27 N., R. 18 E., MDM, NEVADA

CHAINS		
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R18E R19E ¼ S 12 S 7</p> <p style="text-align: center;">1973</p> <p>deposit the original cornerstone, broken glass and set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p> <hr/> <p>N. 0° 16' W., beginning new measurement.</p> <p>Ascend 60 ft. over gradual WSW. slope changing to SW. slope.</p> <p>40.30 The cor. of secs. 1, 6, 7 and 12, monumented with a volcanic stone, 16x10x5 ins., firmly set 8 ins. in the ground, mkd. with 5 grooves on the S. face and 1 groove on the N. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R18E R19E S 1 S 6 S 12 S 7</p> <p style="text-align: center;">1973</p> <p>deposit the original cornerstone, broken glass and set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p>	
	<p>N. 0° 12' E., bet. secs. 1 and 6.</p> <p>Over rolling land, covered with medium sagebrush and greasewood; asc. 110 ft. over SW. slope.</p> <p>26.00 Base of mountains; asc. 60 ft. over SW. slope.</p> <p>36.10 Wash, 20 lks. wide, 4 ft. deep, drains SSW.; asc. 50 ft. over SW. slope.</p> <p>39.47 The ¼ sec. cor. of secs. 1 and 6, monumented with a volcanic stone, 26x14x12 ins., firmly set in a mound of stone, mkd. ¼ on the W. face.</p> <p>At the corner point</p>	