

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
T. 27 N., R. 18 E., MDM, NEVADA

CHAINS	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div>T28N R18E S 33 ¼ S 4 T27N 1973</div> <p>set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p>
	<p>80.56 The cor. of secs. 4, 5, 32 and 33, monumented with a volcanic stone, 16x8x4 ins., firmly set 8 ins. in the ground, mkd. with 4 grooves on the E. face and 2 grooves on the W. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div>T28N R18E S 32   S 33 S 5   S 4 T27N 1973</div> <p>deposit the original cornerstone, broken glass and set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p> <hr/> <p>WEST, bet. secs. 5 and 32.</p> <p>Over gently rolling land.</p>
	<p>40.25 The ¼ sec. cor. of secs. 5 and 32, monumented with a volcanic stone, 16x12x5 ins., firmly set 8 ins. in the ground, mkd. ¼ on the N. face. (Record wooden post).</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div>T28N R18E S 32 ¼ S 5 T27N 1973</div> <p>deposit the original cornerstone, broken glass and set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p> <hr/>