

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 29 N., R. 18 E., MDM, NEVADA

CHAINS	
	deposit the original cornerstone and set a steel fence post, 6 ft. long, 1 ¹ / ₄ ins. in the ground, alongside the iron post.
	From this corner, a spring, bears N. 7° E., 14.70 chs. dist.
	N. 0° 15' W., bet. secs. 2 and 3.
	Over rolling land, covered with medium sagebrush and bunchgrass; desc. 100 ft. over W. slope.
11.60	Ravine, drains SW.; asc. 140 ft. over S. slope.
33.00	Spur, slopes W.; desc. 20 ft. over N. slope.
40.02	The ¹ / ₄ sec. cor. of secs. 2 and 3, monumented with a basalt stone, 20x10x8 ins., firmly set in a mound of stone, mkd. ¹ / ₄ on the W. face.
	At the corner point
	Set an iron post, 28 ins. long, 2 ¹ / ₂ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd.
	T29N R18E ¹ / ₄ S 3 ¹ / ₂ S 2
	1973
	deposit the original cornerstone and set a steel fence post, 6 ft. long, 6 ins. in the ground, alongside the iron post.
	N. 0° 32' W., beginning new measurement.
	Descend 210 ft. over N. slope.
31.70	Ravine, drains WSW.; asc. 330 ft. over S. slope.
55.50	Spur, slopes W.; desc. 70 ft. over W. slope.
63.29	The cor. of secs. 2, 3, 3 ¹ / ₄ and 35, on the N. bdy. of the Tp., monumented with an iron post, 2 ¹ / ₂ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the resurvey of the S. bdy. of T. 30 N., R. 18 E., resurveyed concurrently under this same group.
	From the cor. of secs. 2, 3, 10 and 11.
	S. 89° 59' W., bet. secs. 3 and 10.
	Over rolling land, covered with medium sagebrush and bunchgrass; desc. 220 ft. over W. slope.