

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 29 N., R. 18 E., MDM, NEVADA

CHAINS	
	N. 0° 08' E., bet. secs. 3 and 4.  Over rolling land, covered with medium sagebrush and bunchgrass; asc. 50 ft. over E. slope.
8.00	Spur, slopes NE.; desc. 150 ft. over N. slope.
31.80	Draw, drains WSW.; asc. 30 ft. over S. slope.
40.21	The $\frac{1}{4}$ sec. cor. of secs. 3 and 4, monumented with a basalt stone, 22x8x6 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on the W. face.  At the corner point  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd.  T29N R18E $\frac{1}{4}$ S 4 S 3  1973  deposit the original cornerstone and set a steel fence post, 6 ft. long, 12 ins. in the ground, alongside the iron post.
	<hr/>
	N. 0° 23' W., beginning new measurement.  Ascend 250 ft. over S. slope.
30.00	Spur, slopes W.; desc. 60 ft. over N. slope.
41.00	Ravine, drains W.; asc. 80 ft. over S. slope.
56.00	Spur, slopes SSW.; over W. slope.
63.10	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the resurvey of the S. bdy. of T. 30 N., R. 18 E., resurveyed concurrently under this same group.
	<hr/>
	From the cor. of secs. 8, 9, 16 and 17, monumented with a basalt stone, 38x10x10 ins., firmly set in a mound of stone, mkd. with 4 grooves on the S. face and 4 grooves on the E. face.  At the corner point  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.