

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 29 N., R. 18 E., MDM, NEVADA

CHAINS	
	<p>T29N R18E S 8 S 9 S 17 S 16</p> <p>1973</p> <p>deposit the original cornerstone and set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.</p> <p>S. 89° 52' W., bet. secs. 8 and 17.</p> <p>Over gently rolling land, covered with medium sagebrush and bunchgrass.</p>
23.00	Wash, 80 lks. wide, 2 ft. deep, drains S.
39.93	<p>The $\frac{1}{4}$ sec. cor. of secs. 8 and 17, monumented with a basalt stone, 14x12x6 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on the N. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 4 ins. in the ground to solid rock and in a mound of stone, 6 ft. base to top, with brass cap mkd.</p> <p>T29N R18E $\frac{1}{4}$ S 8 S 17</p> <p>1973</p> <p>deposit the original cornerstone and set a steel fence post, 6 ft. long, 4 ins. in the ground, alongside the iron post.</p>
	<p>S. 89° 57' W., beginning new measurement.</p> <p>Over gently rolling land.</p>
15.40	Trail road, bears SE. and NW.
30.36	The closing corner of secs. 8 and 17, monumented with a basalt stone, 14x12x6 ins., firmly set in a mound of stone, mkd. CC on the E. face, 4 grooves on the S. face and 2 grooves on the N. face. I add the marks AM and bury the stone 4 ins. below the surface of the ground.
30.84	<p>Intersect the Nevada-California State Line.</p> <p>Point for the closing corner of secs. 8 and 17.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 6 ft. base to top, with brass cap mkd.</p>