## DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,

T. 30 N., R. 18 E., MDM, NEVADA N. 0° 39' W., beginning new measurement. Descend 410 ft. over broken N. slope. 39.38 The cor. of secs. 19, 24, 25 and 30, monumented with a volcanic stone, 16x16x8 ins., firmly set in a mound of stone, mkd. with 2 grooves on the S. face and 4 grooves on the N. face. At the corner point Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd. - T30N R18E R19E S 24 S 19 S 25 S 30 1973 deposit the original cornerstone alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor. DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES T. 30 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA Reestablishment of the Survey Executed by U. S. Deputy Surveyor C. A. Alverson, in 1880. From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp. N. 0° 14' W., bet. secs. 35 and 36. Over mountainous land, covered with medium sagebrush and bunchgrass; asc. 50 ft. over W. slope. 32.50 Ridge, bears W. and SE.; desc. 50 ft. over NW. slope. 40.23 The  $\frac{1}{4}$  sec. cor. of secs. 35 and 36, monumented with a scoria stone, 16x14x8 ins., firmly set in a mound of stone, mkd. 4 on the W. face. At the corner point Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd.