

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 37 N., R. 18 E., MDM, NEVADA

CHAINS	
28.50	Fence, bears E. and W.; enter gently rolling land, covered with medium sagebrush, greasewood and shadscale.
28.60	Trail road, bears E. and W.
40.23	The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., firmly set and exposed 2 ins. above ground, with brass cap mkd. as described in the official record of the 1917 resurvey.
<p>DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 37 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p>Reestablishment of the Survey Executed by G. W. Garside, U. S. Deputy Surveyor in 1880, and Retraced by H. W. Reppert, U. S. Surveyor and L. R. Mercer, U. S. Transitman in 1917.</p>	
<p>From the cor. of Tps. 37 and 38 N., Rs. 18 and 19 E., monumented with a basalt stone, 16x16x6 ins., firmly set in a mound of stone, mkd. with 6 grooves on the N., S., E. and W. faces.</p>	
<p>At the corner point</p>	
<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., on solid rock over a cross (X) and in a mound of stone, 5 ft. base to top, with brass cap mkd.</p>	
<p style="text-align: center;">T38N R18E R19E S 36 S 31 S 1 S 6 T37N 1973</p>	
<p>deposit the original cornerstone alongside the iron post.</p>	
<p>N. 89° 22' W., bet. secs. 1 and 36.</p>	
<p>Over rolling land, covered with medium sagebrush, grease- wood and shadscale.</p>	
40.26	<p>The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, monumented with a trapstone, 18x14x10 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on the N. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>