

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 69 E., MDM, NEVADA

| | |
|--------|---|
| CHAINS | |
| 40.20 | Bladed road, bears ENE. and WSW.; asc. 80 ft. over S. slope. |
| 45.30 | Spur, slopes E.; desc. 60 ft. over N. slope. |
| 50.00 | Ravine, drains E.; asc. 120 ft. over S. slope. |
| 60.20 | Ridge, bears E. and W.; desc. 190 ft. over N. slope. |
| 70.00 | Bladed road, bears E. and W. |
| 79.34 | The cor. of secs. 11, 12, 13 and 14, monumented with an iron pipe, 2½ ins. diam., firmly set, projecting 10 ins. above ground, in a mound of stone, 3 ft. base to top, at corner of fences bearing E., S. and W., with brass cap mkd. |
| | USFS T13N R69E S 11 S 12 S 14 S 13 |
| | 1972 |
| | This position is harmoniously related to other existing original corners and is accepted as the best available evidence of the position of the original corner. |
| | Not remonumented. |
| | From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set in a collar of stone, 4 ft. base to top, with brass cap mkd. as described in the field notes of the resurvey of the W. boundary of T. 13 N., R. 70 E., executed concurrently under this same Group. |
| | N. 89° 55' W., bet. secs. 12 and 13. |
| | Over meadow land; asc. 150 ft. over gradual E. slope to the ¼ sec. cor. |
| 0.20 | Fence, bears N. 86° E. and S. 86° W. |
| 7.40 | Fence, bears N. and S. |
| 20.50 | Creek, 10 lks. wide, 1 ft. deep, course NE. |
| 41.29 | Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner. |
| | Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. |
| | T13N R69E S 12 ¼ S 13 |
| | 1973 |
| | set a steel fence post alongside the iron post. |