

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 69 E., MDM, NEVADA

CHAINS	
27.40	State Highway No. 74, bears N. 69 3/4° E. and S. 69 3/4° W.
29.20	Telephone line, parallels highway; asc. 110 ft. over S. slope.
35.00	Ridge, bears ENE. and WSW.
35.18	<p>The cor. of secs. 1, 2, 11 and 12, monumented with a wooden post, 2x2x24 ins. long, with illegible scribe marks visible, firmly set in a mound of stone. This corner is harmoniously related to other existing original corners and is accepted as the original corner although the record reports a stone was set at this section corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div>T13N R69E S 2 S 1 S 11 S 12</div> <p>1973</p> <p>from this corner, U.S.C. & G.S. triangulation station "LEHMAN 1957," bears N. 88° 30' E., 2.26 chs. dist., monumented with a standard disk, firmly set in a drilled hole in outcropping of bedrock, about ½ ft. above ground, with top mkd. LEHMAN 1957.</p>
	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, 4 ft. base to top, mkd. and witnessed as described in the field notes of the resurvey of the W. bdy. of T. 13 N., R. 70 E., executed concurrently under this same Group.</p> <p>S. 87° 19' W., bet. secs. 1 and 12.</p> <p>Over gently rolling land, through sagebrush.</p>
34.20	Telephone line, bears S. 14¼° E. and N. 14¼° W.
34.80	Improved gravel road, parallels telephone line.
41.19	Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.