

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 69 E., MDM, NEVADA

CHAINS	
11.20	Wash, 20 lks. wide, 3 ft. deep, drains E.; asc. 40 ft. over S. slope.
22.40	Spur, slopes E.
22.70	Fence, bears SE. and NW.; desc. 70 ft. over N. slope.
36.20	Trail road, bears E. and W.
36.70	Fence, bears E. and W.
39.80	Wash, 30 lks. wide, 2 ft. deep, drains E.
46.62	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 4 ft. base to top, with brass cap mkd. as described in the field notes of the resurvey of the subdivisio- nals lines of T. 14 N., R. 69 E., executed con- currently under this same Group.</p> <p>This corner is located alongside a fence corner at the NW. cor. of a cemetery.</p>
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89° 53' W., along the S. bdy. of sec. 11.</p> <p>Over rolling land, through scattered sagebrush and medium juniper and pinon; asc. 180 ft. over gradual E. slope to the ¼ sec. cor.; along fence.</p>
19.70	Cor. of fence, bears N., 0.05 chs. dist., from which fences bears N., E. and W.
40.45	<p>The ¼ sec. cor. of secs. 11 and 14, monumented with an unmarked iron pipe, 2½ ins. diam., firmly set, projecting 16 ins. above a mound of stone. This position is harmon- iously related to other existing original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 2 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div><div>T13N R69E</div><div><div>¼</div><div>S 11</div><div>S 14</div></div></div> <p>1973</p> <p>reset the iron pipe, inverted, alongside the iron post.</p> <p>From this corner, a fence, bearing E. and W., bears N., 0.12 chs. dist.</p>