

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 24 N., R. 54 E., MDM, NEVADA

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T24N R54E ¼ S 3 ----- S 10</p> <p style="text-align: center;">1974</p>
<p>1.60</p> <p>8.60</p> <p>40.02</p>	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 0° 01' W., bet. secs. 3 and 4.</p> <p>Over nearly level land, through rabbitbrush.</p> <p>Gravel road, bears S. 10½° E. and N. 10½° W.</p> <p>Powerline, parallels gravel road.</p> <p>Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24N R54E ¼ S 4   S 3</p> <p style="text-align: center;">1974</p>
<p>68.50</p> <p>72.56</p> <p>80.56</p>	<p>set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Over rolling land, through rabbitbrush and sagebrush; asc. 170 ft. over W. slope.</p> <p>Top of ascent, slopes W.; over broken W. slope.</p> <p>The closing cor. of sec. 33, T. 25 N., R. 54 E., monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone and mkd. as described in the field notes of T. 25 N., R. 54 E., executed concurrently under this same group.</p> <p>Along the E. bdy. of sec. 4, continuing measurement.</p> <p>The cor. of sec. 4, on the N. bdy. of the Tp.</p> <hr/> <p>The cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set and exposed 4 ins. above ground, with brass cap mkd. as described in the field notes of T. 23 N., R. 54 E., executed concurrently under this same group.</p>