

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 25 N., R. 54 E., MDM, NEVADA

CHAINS		
39.98	<p>S. 0° 03' W., bet. secs. 32 and 33.</p> <p>Over nearly level land, through sagebrush and rabbitbrush.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 32 and 33, monumented with an iron post, 1 in. diam., firmly set and exposed 16 ins. above ground, with brass cap mkd. as described in the official record of T. 25 N., R. 54 E., executed under Group No. 94, in 1921.</p> <p>Add the marks for T. 25 N., R. 54 E.; the brass cap is now marked.</p> <div style="text-align: center;"> <math>\frac{1}{4}</math>  T25N   R54E  S 32   S 33    1974  1921 </div> <p>set a steel fence post, 5½ ft. long, 12 ins. in the ground, alongside the iron post and raise a collar of stone, around the iron post.</p>	
32.07	<p>S. 0° 02' E., beginning new measurement.</p> <p>Over nearly level land, through rabbitbrush, sagebrush and greasewood.</p> <p>Point for the closing corner of secs. 32 and 33, at intersection with the N. bdy. of sec. 4, T. 24 N., R. 54 E.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> C C  T25N   R54E  S 32   S 33  S 4  T24N R54E    1974 </div> <p>bury a stone, 10x8x6 ins., mkd. X alongside the iron post.</p> <p>The corner is located in a fence, bearing E. and W.</p> <p>From this corner, the cor. of secs. 4, 5, 32 and 33, now an amended monument, monumented with an iron post, 2 ins. diam., firmly set and exposed 12 ins. above ground, with brass cap mkd. as described in the official record of T. 25 N., R. 54 E., executed under Group No. 94, in 1921, bears S. 0° 02' E., 7.87 chs. dist.; add the marks AM and 1974 and raise a collar of stone around the iron post.</p>	