

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 25 N., R. 54 E., MDM, NEVADA

CHAINS	
	<p style="text-align: center;">T25N R54E $\frac{1}{4}$ S 31 S 32</p>
	<p style="text-align: center;">1974 1921</p>
	<p>bury a granite stone, 10x10x2 ins., mkd. X alongside the iron post and raise a collar of stone around the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>SOUTH, beginning new measurement.</p>
	<p>Over nearly level land, through greasewood.</p>
32.20	<p>Fence, bears E. and W.</p>
32.84	<p>Point for the closing corner of secs. 31 and 32, at intersection with the N. bdy. of sec. 5, T. 24 N., R. 54 E.</p>
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">C C T25N R54E <u>S 31 S 32</u> S 5 T24N R54E</p>
	<p style="text-align: center;">1974</p>
	<p>bury a stone, 10x8x4 ins., mkd. X and set a steel fence post, $5\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.</p>
	<p>From this corner, the cor. of secs. 5, 6, 31 and 32, now an amended monument, monumented with an iron post, 2 ins. diam., firmly set and exposed 10 ins. above ground, with brass cap mkd. as described in the official record of T. 25 N., R. 54 E., executed under Group No. 94, in 1921, bears SOUTH, 7.13 chs. dist.; add the marks AM and 1974 and raise a collar of stone around the iron post.</p>
	<p>From this same corner, the $\frac{1}{4}$ sec. cor. of sec. 5, T. 24 N., R. 54 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 24 N., R. 54 E., executed under this same group, bears N. $89^{\circ} 20'$ E., 16.34 chs. dist.</p>
	<hr/>
	<p>The point for the S. $\frac{1}{4}$ sec. cor. of sec. 32, is on the N. and S. centerline of sec. 32 at intersection with the N. bdy. of sec. 5, T. 24 N., R. 54 E.</p>