

Subdivision of Sec. 4, T. 14 N., R. 41 E.,
Mount Diablo Meridian, Nevada

CHAINS		
	From the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.	
	N. $0^{\circ} 33'$ E., on the N. and S. center line of sec. 4.	
	Descend over N. slope, through sagebrush.	
5.80	Wash, 10 lks. wide, drains N. 33° W.; continue to descend over N. slope.	
10.70	Wash, 15 lks. wide, drains N. 54° W.; ascend over SW. slope.	
13.20	Top of ascent, slopes NW.; descend along broken NW. slope.	
19.95	Point for the center south $\frac{1}{16}$ sec. cor. of sec. 4.	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, supported by a mound of stone, 3 ft. base, to top, with brass cap mkd.	
	C S $\frac{1}{16}$ S 4 C 1974	
24.30	Barbed wire fence, 4 strands, bears S. 70° E. and N. 70° W.	
38.20	Wash, 10 lks. wide, drains W.; ascend over S. slope.	
39.90	Point for the center $\frac{1}{4}$ sec. cor. of sec. 4, at intersection with the E. and W. center line.	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, to bedrock, supported by a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd.	
	T 14 N R 41 E C $\frac{1}{4}$ S 4 1974	
41.70	Wash, 10 lks. wide, drains W.; continue to descend over broken NW. slope.	
71.50	Wash, 10 lks. wide, drains N. 28° W.; continue to descend over NW. slope.	
80.02	The $\frac{1}{4}$ sec. cor. of secs. 4 and 33.	
	From the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, monumented with a granite stone, 10 x 8 x 6 ins., mkd. $\frac{1}{4}$ on the W. face, firmly set in a mound of stone, $2\frac{1}{2}$ ft. base.	
	At the corner point	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, to bedrock, supported by a mound of stone, 3 ft. base, to top, with brass cap mkd.	
	T 14 N R 41 E $\frac{1}{4}$ S 4 S 3 1974	