

Subdivision of Section 10,  
T. 34 N., R. 55 E., Mount Diablo Meridian, Nevada

CHAINS	
	From the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.
	N. $0^{\circ} 30'$ W., on the N. and S. center line of sec. 10.
	Over nearly level land, through moderate sagebrush.
0.87	Fence, 4-strand barbed wire, bears N. $40^{\circ}$ E. and S. $40^{\circ}$ W., enclosing Indian cemetery; leave cemetery and continue through residential and school area by traverse.
17.40	Eightmile Creek, 10 lks. wide, course E.
19.86	Point for the center S. $1/16$ sec. cor. of sec. 10; no permanent monument established.
39.00	Fence, 3-strand barbed wire, bears E. and W.
39.72	The center $\frac{1}{4}$ sec. cor. of sec. 10, at intersection with the E. and W. center line, and monumented with a brass cap embedded in cement and encased in a 10 in. diam., steel pipe, set 3 ins. below the surface of an asphalt road; brass cap mkd.
	SURVEY NO C $\frac{1}{4}$ S 10 CHILTON ENGINEERING RLS 1404 ELKO NEVADA
	This cor. was established by Mark Chilton, Nevada Registered Land Surveyor No. 1404, and is accepted as a careful and faithful determination of the position of the center $\frac{1}{4}$ sec. cor. Located under utility line, 6 wires, bearing E. and W., and on the S. edge of asphalt road.
	<hr style="width: 20%; margin: auto;"/>
	N. $0^{\circ} 30'$ W., beginning new measurement.
	Ascend over gentle S. slope, through moderate sagebrush.
0.10	Asphalt road, 50 lks. wide, bears N. $65^{\circ}$ E. and S. $42^{\circ}$ W.
0.836	Intersect the northerly right-of-way of Interstate Highway No. 80, at the point described in the Easement Deed, dated June 24, 1970, between the United States of America and the State of Nevada, Department of Highways, for Parcel 875 B, recorded in Book 127, Page 434, of the Elko County records.
	At the intersection point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.
	S 10   E.I.C.   I-80 1974
	Cor. is located at the cor. of fences, 4-strand barbed wire, bearing N. $8^{\circ}$ W. and S. $80^{\circ}$ E.; also, utility line, 6 wires, bearing S. $45^{\circ}$ E. and N. $45^{\circ}$ W.
14.40	Lot cor. for a subdivision, monumented with a $\frac{1}{2}$ in. diam., rebar.
20.32	Point for the center N. $1/16$ sec. cor. of sec. 10.