DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 45 N., R. 53 E., MDM, NEVADA

	T. 45 N., R. 53 E., MDM, NEVADA
CHAINS	S. 89° 25' W., along the N. bdy. of sec. 1.
	Over rolling land, through sagebrush and bunchgrass.
7• 95	Corner No. 8, Philadelphia Placer, M.S. 2148, monumented with a 4x4 in. wooden post, 2 ft. long, rotted off at ground level, scribed 8 M.S. 2148, on one side.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to solid rock and in a collar of stone, 3 ft. base to top, with brass cap mkd.
	TR37 P-8 MS 2148
	1974
	reset the wooden post and set a steel fence post, 6 ft. long, alongside the iron post.
	From this corner, a steel pipe, 1½ ins. diam., showing 3½ ft. above ground, bears North, .012 chs. dist.
	This corner is located on a spur, sloping S.; desc. 130 ft. over SW. slope.
26.66	Point for Cor. No. 1, H.E.S. No. 76, identical with Angle Point No. 4, Tract 37, at proportionate distance; there is no remaining evidence of the original corner. Corner point falls in dirt road bearing SSE. and NNW.
	Set a 60 penny nail, 6 ins. below surface of road.
	from which
	An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, for a reference monument, bears N. 17° 00' E., 58.2 lks. dist., with brass cap mkd. AP4 TR37 RM 1974 and an arrow pointing to the cor.
	An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, for a reference monument, bears N. 64° 00' W., 84.7 lks. dist., with brass cap mkd. 1 HES 76 RM 1974 and an arrow pointing to the cor.
28.95	Highway No. 51 on curve, bears SSE. and NNW.
29.35	Fence and powerline, bear SSE. and NNW.; enter meadow.
37.715	Point for the angle point on the S. bdy. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.