

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 33 N., R. 32 E., MDM, NEVADA

CHAINS  
41.06

The original  $\frac{1}{4}$  sec. cor. of secs. 35 and 36, monumented with a willow post, 16 ins. long,  $1\frac{1}{2}$  ins. diam., loosely set in a mound of earth. No scribe marks visible.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T33N R32E  
 $\frac{1}{4}$   
S 35 | S 36

1974

reset the wooden post and set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.

N.  $0^{\circ} 37'$  W., beginning new measurement.

Over nearly level land.

39.09

The original corner of secs. 25, 26, 35 and 36, monumented with a willow post, 16 ins. long, 1 in. diam., loosely set in a mound of earth. No scribe marks visible.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T33N R32E  
S 26 | S 25  
S 35 | S 36

1974

reset the wooden post and set a steel fence post, 6 ft. long, 22 ins. in the ground,, alongside the iron post.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. bdy. of T. 33 N., R. 33 E., resurveyed concurrently under Group No. 498.

S.  $89^{\circ} 53'$  W., bet. secs. 25 and 36.

Over nearly level land, through scattered greasewood, budsage and shadscale.

13.60

Trail road, bears NW. and SE.