

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 33 N., R. 32 E., MDM, NEVADA

CHAINS	
	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. bdy. of T. 33 N., R. 33 E., resurveyed concurrently under Group No. 498.</p> <p>N. 89° 56' W., bet. secs. 24 and 25.</p> <p>Over nearly level land, through scattered greasewood, budsage and shadscale.</p> <p>39.96 Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T33N R32E</p> <p>¼ <u>S 24</u></p> <p>S 25</p> <p>1974</p> </div> <p>set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p>
	<p>79.92 The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>N. 0° 02' E., bet. secs. 23 and 24.</p> <p>Over nearly level land, through scattered greasewood, budsage and shadscale.</p> <p>40.31 Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T33N R32E</p> <p>¼</p> <p>S 23 S 24</p> <p>1974</p> </div> <p>set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p>
	<p>52.70 Improved road, bears E. and W.</p>
	<p>80.62 The original corner of secs. 13, 14, 23 and 24, monumented with a willow post, 10 ins. long, 1½ ins. diam., loosely set in a mound of earth. No scribe marks visible.</p>