DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 33 N., R. 32 E., MDM, NEVADA

		T. 33 N., R. 32 E., MDM, NEVADA
<u></u>	CHAINS	S. 89° 53' W., bet. secs. 1 and 12.
		Over nearly level land, through scattered greasewood, budsage and shadscale.
	39.70	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
		T33N R32E <u>1<sub>4</sub> S 1</u> S 12
		1974
		set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.
	79.40	The cor. of secs. 1, 2, 11 and 12.
		N. 0° 38' W., bet. secs. 1 and 2.
		Over nearly level land, through scattered greasewood, budsage and shadscale.
	40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at propor- tionate distance; there is no remaining evidence of the original corner.
		Set an iron post, 28 ins. long, $2^{l_2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
		T33N R32E
		5 2 S 1
		1974
		set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.
	79.82	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp.
		From the cor. of secs. 2, 3, $3^4$ and 35, on the S. bdy. of the Tp., monumented with an iron post, $2^{\frac{1}{2}}$ ins. diam., exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the N. bdy. of T. 32 N., R. 32 E., resurveyed con- currently under Group No. 498.
		N. 0° 06' W., bet. secs. 34 and 35.
		Over nearly level land, through scattered greasewood, budsage and shadscale.