

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 33 N., R. 32 E., MDM, NEVADA

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R32E S 2 ¼ ——— S 11</p> <p style="text-align: center;">1974</p> <p>set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p> <p>43.70 Trail road, bears NNW. and SSE.</p> <p>79.52 The cor. of secs. 2, 3, 10 and 11.</p>	
	<p>N. 1° 06' W., bet. secs. 2 and 3.</p> <p>Over nearly level land, through scattered greasewood, budsage and shadscale.</p> <p>40.79 The original ¼ sec. cor. of secs. 2 and 3, monumented with a willow post, 14 ins. long, 2 ins. diam., loosely set in a mound of earth. No scribe marks visible.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R32E ¼ S 3 S 2</p> <p style="text-align: center;">1974</p> <p>reset the wooden post and set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p> <p style="text-align: center;">—————</p> <p>N. 0° 56' W., beginning new measurement.</p> <p>Over nearly level land.</p> <p>38.60 Trail road, bears NNE. and SSW.</p> <p>38.96 The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp.</p>	
	<p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the N. bdy. of T. 32 N., R. 32 E., resurveyed concurrently under Group No. 498.</p> <p>N. 0° 10' W., bet. secs. 33 and 34.</p>	