

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 33 N., R. 32 E., MDM, NEVADA

CHAINS		
	<p>from this corner</p> <p>A U.S.G.S bench mark, monumented with a standard brass tablet stamped 26 LRC 4294 1971, bears N. 80° 31' E., 15.00 chs. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 31' W., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>39.83 The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp.</p>	
	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the N. bdy. of T. 32 N., R. 32 E., resurveyed concurrently under Group No. 498.</p> <p>N. 0° 56' W., bet. secs. 32 and 33.</p> <p>Over gently rolling land, through scattered greasewood, budsage and shadscale, along general E. slope.</p> <p>38.70 Trail road, bears NW. and SE.</p>	
	<p>39.73 Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R32E ¼ S 32   S 33</p> <p style="text-align: center;">1974</p> <p>set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p>	
	<p>44.80 Trail road, bears E. and W.</p> <p>79.46 The original corner of secs. 28, 29, 32 and 33, monumented with a willow post, 16 ins. long, 2 ins. diam., loosely set in a mound of earth. No scribe marks visible.</p>	
	<p>At the corner point</p>	