

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 33 N., R. 32 E., MDM, NEVADA

CHAINS	
40.42	<p>N. 0° 10' E., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp.</p>
16.50	<p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., exposed 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the N. bdy. of T. 32 N., R. 32 E., resurveyed concurrently under Group No. 498.</p> <p>N. 0° 55' W., bet. secs. 31 and 32.</p> <p>Over gently rolling land, through scattered greasewood, budsage and shadscale, along gradual E. slope.</p> <p>Trail road, bears E. and W.</p>
30.00	<p>Wash, 30 lks. wide, 5 ft. deep, drains E.</p>
40.09	<p>Point for the ¼ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R32E ¼ S 31   S 32</p> <p style="text-align: center;">1974</p> <p>set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p>
45.00	<p>Trail road, bears E. and W.</p>
80.18	<p>Point for the cor. of secs. 29, 30, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T33N R32E S 30   S 29 S 31   S 32</p> <p style="text-align: center;">1974</p> <p>set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p>