

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 32 N., R. 32 E., MDM, NEVADA

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T32N R32E <u>¼ S 32</u></p> <p style="text-align: center;">1974</p> <p>reset the original wooden post and set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 32' W., beginning new measurement.</p> <p>Over gradual E. slope, through budsage, shadscale and greasewood.</p>
32.00	Trail road, bears SSE. and NNW.
40.72	Point for the standard cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T32N R32E <u>S 31 S 32</u></p> <p style="text-align: center;">1974</p> <p>set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.</p>
	<p>S. 89° 32' W., along the S. bdy. of sec. 31.</p> <p>Over gently rolling land, through budsage, shadscale and greasewood.</p>
15.40	Ravine, drains SE.; over broken land, through budsage, shadscale and greasewood; asc. 250 ft. over NE. slope.
40.72	<p>Point for the standard ¼ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>