DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 32 N., R. 32 E., MDM, NEVADA

	T. 32 N., R. 32 E., MDM, NEVADA
CHAINS 40.07	Point for the 4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T32N R32E
	s 14 s 13
	1974
	set a steel fence post, ½ ft. long, 22 ins. in the ground, alongside the iron post.
50.20	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground for a witness point, with brass cap mkd.
	W P T32N R32E S 14 S 13
	1974
	set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.
50.70	High water line of Rye Patch Reservoir, bears irregularly NE. and SW.; across reservoir.
80.14	Point for the cor. of secs. 11, 12, 13 and 14, at proportionate distance; falls in reservoir and not monumented; there is no remaining evidence of the original corner.
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above ground, with steel fence post alongside, with brass cap mkd. as described in the field notes of T. 32 N., R. 33 E., executed concurrently under Group No. 498.
	S. 89° 51' W., bet. secs. 12 and 13.
	Over nearly level land, through greasewood.
27.00	High water line of Rye Patch Reservoir, bears irregularly N. and S.; across reservoir.
39.00	High water line of Rye Patch Reservoir, bears irregularly N. and S.; over nearly level land.
40.07	Point for the 4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.