

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 32 N., R. 32 E., MDM, NEVADA

CHAINS 66.50	High water line of Rye Patch Reservoir, bears irregularly NNE. and SSW.; over gradual E. slope.
67.01	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground for a witness point, with brass cap mkd.
	<p style="text-align: center;">W P T32N R32E <u>    S 2</u> S 11</p>
	1974
	set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.
79.88	The cor. of secs. 2, 3, 10 and 11.
	N. 0° 45' W., bet. secs. 2 and 3.
	Over gradual E. slope, through greasewood.
38.50	Wash, 10 lks. wide, 1 ft. deep, drains irregularly E., soon SE.
39.99	Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p>T32N R32E     ¼ S 3   S 2</p>
	1974
	set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.
69.00	Improved road, bears NE. and SW.
80.05	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with steel fence post alongside, with brass cap mkd. as described in the field notes of T. 32 N., R. 32 E., executed concurrently under Group No. 498.
	From the standard cor. of secs. 33 and 34, on the S. bdy. of the Tp.
	N. 0° 06' W., bet. secs. 33 and 34.
	Over gradual E. slope, through budsage, shadscale and greasewood.