431

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 32 N., R. 32 E., MDM, NEVADA

	T. 32 N., R. 32 E., MDM, NEVADA
CHAINS	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T32N R32E 1 ₄ S 3 5 10
	1974
	set a steel fence post, $5\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.
53.70	Trail road, bears SE. and NW.
58.60	Improved road, bears NE. and SW.
80.32	The cor. of secs. 3, 4, 9 and 10.
	N. 0° 48' W., bet. secs. 3 and 4.
	Over gradual E. slope, through budsage, shadscale and greasewood.
11.00	Wash, 10 lks. wide, 1 ft. deep, drains irregularly E.
25.50	Wash, 30 lks. wide, 2 ft. deep, drains ENE.
27.00	Trail road, bears SE. and NW.
40.15	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T32N R32E ¹ 4 S 4]S 3
	1974
	set a steel fence post, $5\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.
80.21	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above ground, with steel fence post alongside, with brass cap mkd. as described in the field notes of T. 32 N., R. 32 E., executed concurrently under Group No. 498.
	From the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp.
	N. 1° 36' W., bet. secs. 32 and 33.
	Over gradual E. slope, through budsage, shadscale and greasewood.