

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 32 N., R. 32 E., MDM, NEVADA

CHAINS	
	<div>T32N R32E</div> <div>$\frac{1}{4}$</div> <div>S 5 S 4</div> <div>1974</div> <div>set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.</div> <div>48.90Wash, 15 lks. wide, 2 ft. deep, drains irregularly ESE.</div> <div>70.20Trail road, bears ESE. and WNW.</div> <div>80.46The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with steel fence post alongside, with brass cap mkd. as described in the field notes of T. 32 N., R. 32 E., executed concurrently under Group No. 498.</div>
	<div>From the standard cor. of secs. 31 and 32, on the S. bdy. of the Tp.</div> <div>Over gently rolling land, through budsage, shadscale and greasewood.</div> <div>N. 1° 11' W., bet. secs. 31 and 32.</div> <div>11.50Trail road, bears SSE. and NNW.</div> <div>39.92Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</div> <div>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</div> <div><div>T32N R32E</div><div>$\frac{1}{4}$</div><div>S 31 S 32</div><div>1974</div><div>set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.</div><div>42.20Draw, drains E.</div><div>79.84The cor. of secs. 29, 30, 31 and 32, monumented with a nail and washer, firmly set flush with the ground, with a wooden fence post alongside. This point is locally recognized as the corner and is harmoniously related to existing original corners and is accepted as the best available evidence of the position of the original corner.</div><div>At the corner point</div></div>