

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 32 N., R. 32 E., MDM, NEVADA

CHAINS 79.13	<p>The cor. of secs. 30 and 31, on the W. bdy. of the Tp., monumented with a volcanic stone, 18x8x6 ins., firmly set 6 ins. in the ground, plainly mkd. with 1 notch on S. edge and 5 notches on N. edge, with a mound of stone E.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone, 3½ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R31E R32E S 36   S 30           S 31</p> <p>1974</p> </div> <p>bury the marked stone and set a steel fence post, 5½ ft. long, 12 ins. in the ground, alongside the iron post.</p>
37.50	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0° 20' E., bet. secs. 29 and 30.</p> <p>Over gently rolling land, through budsage, shadscale and greasewood.</p>
39.99	<p>Draw, drains ENE.</p> <p>The ¼ sec. cor. of secs. 29 and 30, monumented with a nail and washer, firmly set flush with the ground. This point is locally recognized as the corner and is harmoniously related to existing original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone, 3½ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R32E ¼ S 30   S 29</p> <p>1974</p> </div> <p>bury the nail and washer and set a steel fence post, 5½ ft. long, 12 ins. in the ground, alongside the iron post.</p>
12.00	<p>N. 0° 19' E., beginning new measurement.</p> <p>Over gently rolling land, through budsage, shadscale and greasewood.</p> <p>Trail road, bears E. and W.</p>