

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 32 N., R. 32 E., MDM, NEVADA

<p>CHAINS 39.96</p>	<p>The $\frac{1}{4}$ sec. cor. of secs. 19 and 30, monumented with a galvanized pipe, 12 ins. long, 2 ins. diam., firmly set flush with the ground. This point is locally recognized as the corner and is harmoniously related to existing original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R32E $\frac{1}{4}$ $\frac{S 19}{S 30}$</p> <p>1974</p> </div> <p>reset the galvanized pipe and set a steel fence post, $5\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $89^{\circ} 44'$ W., beginning new measurement.</p> <p>Over gently rolling land, through budsage, shadscale and greasewood.</p>	
<p>39.06</p>	<p>The cor. of secs. 19 and 30, on the W. bdy. of the Tp., monumented with a volcanic rock, 18x10x10 ins., firmly set 8 ins. in the ground, plainly mkd. with 2 notches on S. edge and 4 notches on N. edge, with a mound of stone E.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T32N R31E R32E S 25 $\frac{S 19}{S 30}$</p> <p>1974</p> </div> <p>bury the marked stone alongside the iron post.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. $0^{\circ} 17'$ E., bet. secs. 19 and 20.</p> <p>Over gently rolling land, through budsage, shadscale and greasewood.</p>	