DEPENDENT	RESURVEY	OF THE	SUBDIVISIONAL	LINES,
T. (32 N., R.	32 E.,	MDM, NEVADA	

	T. 32 N., R. 32 E., MDM, NEVADA
chains 40.06	Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T32N R32E 1 S 17 S 20
	1974
	set a steel fence post, $5\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.
80.12	The cor. of secs. 17, 18, 19 and 20.
	N. 89° 56' W., bet. secs. 18 and 19.
	Over gently rolling land, through budsage, shadscale and greasewood.
5.10	Trail road, bears NNE. and SSW.
40.12	Point for the ½ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T32N R32E S 18 S 19
	1974
	set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.
79.40	The cor. of secs. 18 and 19, on the W. bdy. of the Tp., determined at the W. side of a small and partially obliterated mound of stone. No marked stone found. This point is at record bearing and distance from the closing corner of secs. 13 and 24, T. 32 N., R. 31 E., and is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.