DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 1 N., R. 69 E., MDM, NEVADA

CHAINS	
24.30	Spur, slopes NW.; desc. 100 ft. over N. slope to wash.
25.20	Trail road, bears NNW. and SSE.
33.30	Trail road, bears WNW. and ESE.
36.80	Wash, 20 lks. wide, 1 ft. deep, drains W.; asc. 50 ft. over S. slope.
40.24	The cor. of secs. 1, 2, 11 and 12, monumented with a trachyte stone, 16x12x8 ins., firmly set and exposed 12 ins. above ground, plainly mkd. with 5 grooves on S. face and 1 groove on E. face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd. T1N R69E S 2 | S 1 S 11 | S 12 1974 reset the original cornerstone alongside the iron post. from this corner A pinon, 6 ins. diam., bears N. 86½° E., 80 lks. dist., mkd. T1N R69E S1 BT. A pinon, 6 ins. diam., bears S. 3/4° E., 38 lks. dist., mkd. T1N R69E S12 BT. A pinon, 10 ins. diam., bears N. 47 3/4° W., 113 lks. dist., mkd. T1N R69E S2 BT. No other suitable bearing trees available.
	From the cor. of secs. 1 and 12, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., exposed 12 ins. above ground and in a mound of stone to cap, 3 ft. base, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. bdy. of T. 1 N., R. 70 E. S. 88° 04' W., bet. secs. 1 and 12. Over rolling land, through scattered sagebrush, juniper and pinon; asc. 80 ft. over NNE. slope.
35.80	End of spur, slopes NNE.; desc. 30 ft. over W. slope.
39.05	Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.