

Subdivision, Section 6,  
T. 13 N., R. 21 E., Mount Diablo Meridian, Nevada

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, 3½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 13 N    R 21 E C ¼    S 6 1975</p> <p>from which</p> <p style="padding-left: 40px;">A pinon, 9 ins. diam., bears S. 62½° W., 12.5 lks. dist., mkd. X BT.</p>
52.00	Begin ascending across E. slope.
80.81	<p>The ¼ sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, and in a mound of stone, 3½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">¼    <math>\frac{S \ 31}{S \ 6}</math> 1950</p> <p>from which the remaining bearing tree mkd. by Voigt in 1950</p> <p style="padding-left: 40px;">A pinon, 10 ins. diam., bears S. 20° E., 9 lks. dist., mkd. with healed blaze. (Record, S. 26¼° E.)</p>
	<p>From the ¼ sec. cor. of secs. 5 and 6.</p> <p>S. 89° 46' W., on the E. and W. center line of sec. 6.</p> <p>Over nearly level land, through moderate sagebrush.</p>
11.00	Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W.
40.20	Dirt road, 15 lks. wide, bears N. 30° E. and S. 30° W.; begin ascent over SE. slope.
41.47	The center ¼ sec. cor. of sec. 6.
53.80	Spur, slopes SE.; desc. over SW. slope.
63.40	Ravine, drains South; asc. over SE. slope.
72.45	Spur, slopes South; desc. over SW. slope.
78.75	<p>The ¼ sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, in a mound of stone, 3½ ft. base, to top, with brass cap mkd. as described in the field notes of the Hochstrasser 1973 resurvey.</p>