

INDEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL NORTH,  
THROUGH R. 68 E., MDM, NEVADA

CHAINS	
	<p style="text-align: center;">S C T26N R68E <u>S 32   S 33</u></p> <p style="text-align: center;">1975</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>from this corner</p> <p>The original standard corner of secs. 32 and 33, monumented with a squared wooden post, 30 ins. long, 2 ins. square, loosely set in a mound of earth, with illegible scribe marks visible, bears N. 47° 26' W., 1.15 chs. dist.; add the marks AM and bury the post 6 ins. below the surface of the ground.</p> <p>Land, nearly level. Soil, sandy clay. Undergrowth, sagebrush, greasewood and whitesage.</p>
	<p>N. 89° 29' W., along the S. bdy. of sec. 32.</p> <p>Over nearly level land, through scattered undergrowth.</p>
26.70	Wash, 30 lks. wide, 3 ft. deep, drains NE.
40.00	Point for the standard $\frac{1}{4}$ sec. cor. of sec. 32.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">S C T26N R68E <u><math>\frac{1}{4}</math> S 32</u></p> <p style="text-align: center;">1975</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
60.50	Wash, 10 lks. wide, 2 ft. deep, drains NE.
72.00	Bladed road, bears NNE. and SSW.
80.00	Point for the standard corner of secs. 31 and 32.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">S C T26N R68E <u>S 31   S 32</u></p> <p style="text-align: center;">1975</p>