

INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 26 N., R. 68 E., MDM, NEVADA

CHAINS		
	N. 0° 01' E., bet. secs. 1 and 2.	
	Over gently rolling land, through scattered undergrowth.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.	
	T26N R68E	
	$\frac{1}{4}$	
	S 2 S 1	
	1975	
79.99	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., exposed 9 ins. above ground and in a collar of stone, with brass cap mkd. as described in the field notes of the independent resurvey of T. 27 N., R. 68 E., surveyed concurrently under this same Group.	
	Land, gently rolling.	
	Soil, sandy clay.	
	Undergrowth, sagebrush, greasewood and shadscale.	
	From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp.	
	N. 0° 02' W., bet. secs. 34 and 35.	
	Over nearly level land, through scattered undergrowth.	
4.30	Bladed road, bears NE. and SW.	
38.60	Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at 40.00 chs. in latitude from the cor. of secs. 26, 27, 34 and 35.	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	T26N R68E	
	$\frac{1}{4}$	
	S 34 S 35	
	1975	
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.	
78.60	Intersect the sectional correction line.	
	Point for the cor. of secs. 26, 27, 34 and 35.	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.	