

INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 26 N., R. 68 E., MDM, NEVADA

CHAINS	
	<p>T26N R68E  <math>\frac{1}{4}</math>  S 5<math>\frac{1}{2}</math>S 4  1975</p>
80.01	<p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an iron post, 2<math>\frac{1}{2}</math> ins. diam., exposed 4 ins. above ground, with brass cap mkd. as described in the field notes of the independent resurvey of the S. bdy. of T. 27 N., R. 68 E., surveyed concurrently under this same Group.</p> <p>Land, rolling.  Soil, sandy clay and rocky.  Undergrowth, sagebrush and greasewood.</p>
36.55	<p>From the standard corner of secs. 31 and 32, on the S. bdy. of the Tp.</p> <p>N. 0° 04' W., bet. secs. 31 and 32.</p> <p>Over gently rolling land, through scattered undergrowth.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 31 and 32, at 40.00 chs. in latitude from the cor. of secs. 29, 30, 31 and 32.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.</p> <p>T26N R68E  <math>\frac{1}{4}</math>  S 31<math>\frac{1}{2}</math>S 32  1975</p>
42.30	Wash, 20 lks. wide, 3 ft. deep, drains E.
63.30	Wash, 20 lks. wide, 1 ft. deep, drains E.
71.30	Ascend 30 ft. over S. slope.
76.30	Spur, slopes E.; desc. over N. slope.
76.55	Intersect the sectional correction line.
	<p>Point for the cor. of secs. 29, 30, 31 and 32.</p>