

INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 27 N., R. 68 E., MDM, NEVADA

CHAINS	
	<div>T27N R68E</div> <div>S 26   S 25</div> <div>S 35   S 36</div> <div>1974</div> <div>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</div> <div>Land, rolling.</div> <div>Soil, sandy clay and rocky.</div> <div>Undergrowth, greasewood and shadscale.</div>
	<div>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., exposed 6 ins. above ground and in a mound of stone to cap, 3 ft. base, with brass cap mkd. as described in the field notes of the independent resurvey of the W. bdy. of T. 27 N., R. 69 E., surveyed under Group No. 463.</div> <div>WEST, bet. secs. 25 and 36.</div> <div>Over rolling land, through scattered undergrowth; desc. 230 ft. over SW. slope to ¼ sec. cor.</div>
34.50	Trail road, bears N. and S.
40.05	<div>Point for the ¼ sec. cor. of secs. 25 and 36.</div> <div>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone to cap, 5 ft. base, with brass cap mkd.</div> <div><div>T27N R68E</div><div>¼ S 25</div><div>¼ S 36</div><div>1974</div><div>Descend 160 ft. over W. slope.</div></div>
71.00	Trail road, bears NE. and SW.
72.00	Wash, 10 lks. wide, 2 ft. deep, drains SW.
72.50	Trail road, bears NE. and SW.
80.10	<div>The cor. of secs. 25, 26, 35 and 36.</div> <div>Land, rolling.</div> <div>Soil, sandy clay and rocky.</div> <div>Undergrowth, sagebrush and greasewood.</div>
	<div>N. 0° 01' W., bet. secs. 25 and 26.</div> <div>Over rolling land, through scattered undergrowth; asc. 130 ft. over S. slope.</div>