

INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 27 N., R. 68 E., MDM, NEVADA

CHAINS	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R68E S 14 S 13 S 23 S 24</p> <p style="text-align: center;">1974</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, rolling to gently rolling. Soil, sandy clay and rocky. Timber, juniper. Undergrowth, sagebrush and greasewood.</p>	
	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., exposed 6 ins. above ground and in a mound of stone to cap, 3 ft. base, with brass cap mkd. as described in the field notes of the independent resurvey of the W. bdy. of T. 27 N., R. 69 E., surveyed under Group No. 463.</p> <p>S. 89° 59' W., bet. secs. 13 and 24.</p> <p>Over rolling land, through scattered timber and undergrowth; desc. 30 ft. over W. slope.</p>	
6.70	Trail road, bears NE. and SW.	
11.40	Trail road, bears NNW. and SSE.; asc. 50 ft. over E. slope.	
26.00	Low ridge, bears N. and S.; desc. 100 ft. over W. slope.	
40.05	<p>Point for the ¼ sec. cor. of secs. 13 and 24.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T27N R68E ¼ S 13 S 24</p> <p style="text-align: center;">1974</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Descend 40 ft. over W. slope.</p>	
47.30	Wash, 10 lks. wide, 2 ft. deep, drains SW.	
47.50	Trail road, bears NE. and SW.; asc. 20 ft. over SE. slope.	
52.80	Spur, slopes S.; desc. 20 ft. over W. slope.	