

INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 27 N., R. 68 E., MDM, NEVADA

CHAINS	
59.10	Trail road, bears NNW. and SSE.; asc. 190 ft. over E. slope.
79.92	The cor. of secs. 7, 8, 17 and 18. Land, nearly level and rolling. Soil, sandy clay. Undergrowth, whitesage.
	WEST, bet. secs. 7 and 18. Over rolling land, through scattered undergrowth.
0.60	Spur, slopes NE.; desc. 120 ft. over NW. slope.
40.00	Point for the cor. of secs. 7 and 18. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T27N R68E $\frac{1}{4} \begin{array}{r} S \quad 7 \\ S \quad 18 \end{array}$ 1974 </div>
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Over nearly level land.
48.50	Trail road, bears NE. and SW.
64.80	Trail road, bears NNE. and SSW.
71.50	Wash, 40 lks. wide, 4 ft. deep, drains N.
79.92	Intersect the E. bdy. of sec. 13, T. 27 N., R. 67 E. Point for the closing corner of secs. 7 and 18. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T27N T27N R68E S 13 $\begin{array}{r} S \quad 7 \\ S \quad 18 \end{array}$ CC R67E 1974 </div>
	raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor. From this corner, the cor. of secs. 12 and 13, T. 27 N., R. 67 E., bears N. 0° 24' E., 6.04 chs. dist. Land, rolling to nearly level. Soil, sandy clay and rocky. Undergrowth, greasewood and shadscale.