	INDEPENDENT RESURVEY OF THE NORTH BOUNDARY, T. 28 N., R. 68 E., MDM, NEVADA
CHAINS	1. 20 N., N. OO H., IMM, REVIEW
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T29N R68E <u>S 31 S 32</u> S 6 S 5 T28N
	1975
	raise a mound of stone, 4 ft. base, 2 ft. high, W. of cor.
	From this corner, the original cor. of secs. 5, 6, 31 and 32, monumented with a wooden post, 25 ins. long, 2 ins. square, with illegible scribe marks visible, firmly set alongside a steel fence post, bears N. 16° 27' E., 14.81 chs. dist. Add the marks AM and bury the wooden post 6 ins. below the surface of the ground.
	Land, nearly level. Soil, sandy clay. Undergrowth, sagebrush, whitesage and shadscale.
	WEST, bet. secs. 6 and 31, on a transit line describing the secant, which bears S. 89° 58.5' W.
	Over nearly level land, through medium undergrowth.
40.00	Point for the 4 sec. cor. of secs. 6 and 31, North 2 lks. from the secant.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T29N R68E \(\frac{\text{S} \text{ 31}}{\text{S} \text{ 6}} \) T28N
	1975
	raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.
76.99	Intersect the E. bdy. of sec. 1, T. 28 N., R. 67 E.
	Point for the closing corner of Tps. 28 and 29 N., R. 68 E., North 4 lks. from the secant.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T28N T29N R67E R68E S 1 S 31 CC T28N
	1975

1975

raise a mound of stone, 3 ft. base, 2 ft. high, ${\tt E.}$ of cor.