

INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 28 N., R. 68 E., MDM, NEVADA

CHAINS 80.00	<p>Point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to cap, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T28N</td><td>R68E</td></tr> <tr><td>S 26</td><td>S 25</td></tr> <tr><td>S 35</td><td>S 36</td></tr> </table> <p>1975</p> </div> <p>Land, rolling. Soil, sandy clay and rocky. Timber, juniper and pinon. Undergrowth, sagebrush, shadscale and bunchgrass.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, 4 ft. base to cap, with brass cap mkd. as described in the field notes of the independent resurvey of the W. bdy. of T. 28 N., R. 69 E., surveyed under Group No. 463.</p> <p>N. 89° 53' W., bet. secs. 25 and 36.</p> <p>Over rolling land, through timber and undergrowth; desc. 100 ft. over NW. slope.</p>	T28N	R68E	S 26	S 25	S 35	S 36
T28N	R68E						
S 26	S 25						
S 35	S 36						
15.00	Bottom of descent; asc. 40 ft. over E. slope.						
26.40	Trail road, on curve, bears NNE. and SW.						
40.03	<p>Point for the ¼ sec. cor. of secs. 25 and 36.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T28N</td><td>R68E</td></tr> <tr><td>¼</td><td>S 25</td></tr> <tr><td></td><td>S 36</td></tr> </table> <p>1975</p> </div> <p>raise a mound of stone, 4 ft. base, 2 ft. high, N. of cor.</p> <p>Ascend 100 ft. over E. slope changing to SE. slope.</p>	T28N	R68E	¼	S 25		S 36
T28N	R68E						
¼	S 25						
	S 36						
80.06	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, mountainous. Soil, sandy clay and rocky. Timber, juniper and pinon. Undergrowth, sagebrush and greasewood.</p>						