

INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 28 N., R. 68 E., MDM, NEVADA

CHAINS	
	Ascend 30 ft. over S. slope.
43.20	Spur, slopes SE.; desc. 150 ft. over NE. slope.
50.70	Ravine, drains SE.; asc. 320 ft. over S. slope.
63.50	Ridge, bears E. and N.; desc. 110 ft. along E. side of ridge.
77.30	Ravine, drains ESE.; asc. 40 ft. over SE. slope.
80.00	Point for the cor. of secs. 13, 14, 23 and 24.
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to cap, with brass cap mkd.
	<div style="text-align: center;"> T28N R68E S 14 S 13 S 23 S 24 </div>
	1975
	This corner is located in a small draw draining SSE.
	Land, mountainous.
	Soil, sandy clay and rocky.
	Timber, juniper and pinon.
	Undergrowth, sagebrush, bitterbrush and bunchgrass.
	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, 4 ft. base to cap, with brass cap mkd. as described in the field notes of the independent resurvey of the W. bdy. of T. 28 N., R. 69 E., surveyed under Group No. 463.</p>
	N. 89° 48' W., bet. secs. 13 and 24.
	Over mountainous land, through medium timber and undergrowth; asc. 250 ft. over ESE. slope.
21.70	Spur, slopes SE.; desc. 250 ft. over W. slope.
33.90	Ravine, with wash in bottom, 30 lks. wide, 2 ft. deep, drains SE.; asc. 140 ft. over E. slope.
40.03	Point for the ¼ sec. cor. of secs. 13 and 24.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T28N R68E S 13 ¼ ——— S 24 </div>
	1975
	raise a mound of stone, 4 ft. base, 2 ft. high, N. of cor.